

Ad-hoc Connection Between Electronic Devices

FIELD OF THE INVENTION

5 The invention relates to a method of creating an ad-hoc
connection between at least two electronic devices for
enabling an interaction between the at least two
electronic devices. The invention relates equally to a
corresponding device and to a corresponding software
10 program product.

BACKGROUND OF THE INVENTION

A mobile electronic device often travels along with its
15 user from place to place. Each day, the user encounters
dozens or even hundreds of other electronic devices
having the potential to communicate with the mobile
electronic device. The user meets for instance other
people carrying their own mobile electronic devices,
20 visits places equipped with consumer or office
electronics, or passes by a store that provides
electronic services or marketing.

There exist powerful user interface (UI) concepts which
25 can be used in communications between different
electronic devices, such as cut-and-paste, copy-and-paste
and drag-and-drop concepts. These concepts provide very
intuitive possibilities of interconnecting different
applications even across different electronic devices.
30 For instance, it is a simple task to drag-and-drop a file
from the disk of one computer to the disk of another
computer, provided that the computers are first connected
to each other.

Before a user can make his or her mobile electronic device interact with an encountered electronic device, an ad-hoc connection has thus to be established first.

- 5 Most prior art approaches require the user to create an ad-hoc connection in a way that is specific to the connection technology. The creation of the ad-hoc connection may also be separated completely from the task for which the connection is desired.

10

For example, the user of a laptop computer may start a card manager application for activating a Wireless Local Area Network (WLAN) card and select the correct connection profile and/or access point. When making an
15 ad-hoc connection, the user may even have to create a new connection profile. Finding the necessary parameters for the connection profile is a challenge of its own.

20

Unless the user encounters the same electronic device almost every day, it is therefore unlikely that the user bothers or is in a position to connect his or her mobile electronic device to some encountered device.

25

Also if the possibility of establishing a connection is integrated into an application, the user of known devices has to follow a complex menu structure until the right menu item is found. In general, it is a target to allow a desired item to be reached with as few clicks as possible, but due to the large amount of functions, there
30 are usually nevertheless several clicks needed to reach a desired item.

In a typical situation in which content is to be shared or exchanged between the electronic devices of two users,

somebody takes a picture with a DSC or a camera enabled mobile phone and desires to share the picture with another person close by. To send the item over a short-range technology, like Bluetooth™, the person has to
5 select the right menu item in the device, address the other device, typically by first searching or inquiring the device, select the device and then transmit the picture file to the other device. This requires a couple of steps, and for many technically inexperienced end
10 users, this will be a burden in actually using an available function.

SUMMARY OF THE INVENTION

15 It is an object of the invention to enable the creation of ad-hoc connections between electronic devices in a particularly user-friendly way.

A method of creating an ad-hoc connection between at
20 least two electronic devices for enabling an interaction between the at least two electronic devices is proposed, which comprises at a first one of the electronic devices detecting a hugging state between the first electronic device and a second one of the electronic devices. A
25 hugging state is assumed to be given if the first electronic device and the second electronic device are at least in close vicinity to each other and a piece of information is received at the first electronic device directly from the second electronic device. The proposed
30 method further comprises, in case a hugging state is detected, obtaining a handle proceeding from the received piece of information. The handle comprises at least an address of at least one other of the at least two electronic devices than the first electronic device. Such

another electronic device can thus be either the second electronic device or a further electronic device. The proposed method finally comprises establishing a communication channel between the first electronic device and the at least one other of the electronic devices
5 using the address included in the handle.

Moreover, an electronic device is proposed, which comprises a touch detection portion and a link creation
10 portion. The touch detection portion is adapted to detect a hugging state between the electronic device and a further electronic device. A hugging state is assumed to be given if the electronic device and the further electronic device are at least in close vicinity to each
15 other and a piece of information is received by the electronic device directly from the further electronic device. The touch detection portion is further adapted to obtain a handle proceeding from a piece of information received from a further electronic device in case a
20 hugging state is detected. The handle comprising at least an address belonging to at least one electronic device other than the proposed electronic device. The link creation portion is adapted to establish a communication channel to at least one other electronic device using an
25 address included in a handle provided by the touch detection portion for enabling an interaction with the at least one other electronic device.

Moreover, an expandable framework for an electronic
30 device is proposed, which comprises a touch detection portion, a link creation portion and an additional control portion. The touch detection portion and the link creation portion, which correspond to the touch detection portion and the link creation portion of the proposed

electronic device, are connected to the additional control portion. The additional control portion is adapted to be supplemented by functional blocks supporting a respective service, and comprises at least
5 one interface for enabling an input to functional blocks added to the additional control portion.

Finally, a software program product is proposed, in which a software code for creating an ad-hoc connection between
10 at least two electronic devices for enabling an interaction between the at least two electronic devices is stored. The software code realizes the steps of the proposed method when running in a first one of the electrical devices.

15 The invention proceeds from the consideration that a user may physically indicate by touching, pointing, etc., that two devices should be connected to each other so that they can share information or otherwise interact. A piece
20 of information transmitted during such an indication can then be employed by one of the devices for determining an address of the other device. Thereby, the device is able to automatically establish a communication channel to this address. The invention relies on a concept which is
25 referred to as "hugging". The exact definition of this term and thus of the required criteria may vary. In the most general case, the "hugging" only needs to enable one electronic device to determine that another electronic device, which is currently nearby, might be willing to
30 interact.

A subsequent interaction on an established communication channel is advantageously context dependent. An interaction is considered to be context dependent if the

nature of the interaction depends on the state of either of the involved electronic devices, on a specific combination of their states and/or on an input to the electronic devices. The nature of the interaction between
5 the electronic devices may also depend on the state of or the input to applications in the devices, on available data and services, on user preferences, etc. An interaction may be content dependent to the effect that it is selected in a context specific way which
10 application within one electronic device is to interact with an application in another device. Similarly, if some additional information is passed to an application, the application is enabled to interact with another application via the communication channel in a context
15 specific way. A context dependent interaction may be caused by any suitable component of the electronic device, for instance the link creation portion, the additional control portion of a provided framework, or an application.

20
Since it is proposed that an address is obtained as part of the handle for establishing a communication channel, the possible communication channels are not limited to direct links between the devices. Rather, any type of
25 direct or indirect communication channel which allows reaching the address in the handle can be employed. That is, after the handle has been obtained, a large distance could be brought in between the involved electronic devices, as an indirect communication channel, for
30 instance via some communication network, can be established. The communication channel uses advantageously, though not necessarily, a link between the involved electronic devices which enables an interaction via the communication channel over any

distance, at least as soon as the involved electronic devices reach a distance to each other which does not permit another type of link for an interaction via the communication channel.

5

It is an advantage of the invention that it allows to unify the user experience of setting up a local or non-local ad-hoc connection across different technologies between electronic devices which are close to each other.

10 If in wide use, the invention even allows unification of the user experience of setting up such a connection across all or almost all electronic devices that a person may own or use.

15 It is further an advantage of the invention that it reduces the amount of user time needed to set up such a connection. The invention makes setting up an ad-hoc connection and using it for a specific purpose a very intuitive, physical and easy experience, as it allows one
20 to avoid having to type through a menu structure. Thus, it improves the usability of electronic devices.

In one embodiment of the invention, a hugging state is assumed to be given if the first and the second
25 electronic devices actually touch each other physically. In order to enable a detection of such a touch, the electronic devices may be provided on their surface with a material ensuring a galvanic contact, for example a metal or a polymer that conducts electricity. A hugging
30 state may also be seen in the act of connecting two devices, for example if a data cable is connected between a mobile phone and PC constituting the electronic devices, an Internet Protocol (IP) connection is opened, a VPN tunnel is set up and a http GET is done. For

instance, a user could connect a desktop computer and a media phone with a data cable for one second and then leave the room taking the media phone along.

5 As an alternative to touching, a hugging state may also be assumed to be given for example if one electronic device, in particular a mobile device, is used for pointing at another electronic device. Such a pointing can be detected for instance by means of an infrared
10 beam, a laser light or an infrasound, which all support passing information for a handle.

As a further alternative to touching, a hugging state may be assumed to be given if one electronic device is
15 brought into close proximity of another device, for example to a distance of 5 to 50 centimeters. Detecting the proximity of another device can be based on the same technologies as detecting a pointing, if means for measuring the distance are added to the electronic
20 devices. In addition, purely non-directional signals, such as those used in WLAN, Bluetooth™ or Radio Frequency Identification (RFID), can be used. At least Bluetooth™ enables a measurement of the distance. More specifically, the distance can be derived from Receive Signal Strength
25 Indicator (RSSI) measurements.

The physical means required for detecting a hugging state thus depend on the respectively supported type or types of hugging which shall be detected. They may comprise a
30 galvanic surface, an infrared (IR) led/detector, an RFID chip, a Bluetooth™ chip, etc. The physical means can be part of an electronic device itself or be built into an accessory, such as snap-on covers of a mobile phone. In addition, a logic can be used to determine that a hugging

is taking place based on the information provided by the physical means.

Typically, the detection of a hugging state does not
5 require user input beyond the actual causing of the hugging state, even though a user input is not excluded.

The handle which is obtained according to the invention can be or comprise, for instance, the IP-address or the
10 Mobile Subscriber Integrated Services Digital Network (MSISDN) of the respective other electronic device.

Gaining the handle may simply comprise receiving such an IP-address or MSISDN of the other electronic device from
15 the second electronic device, or it may involve complex negotiations between the first and the second electronic device for determining the address and possibly other communication parameters for setting up the connection.

20 In some cases, gaining the handle may require multiple steps, for example if RFID is used as technology for detecting a hugging and obtaining a handle.

RFID is a short-range technology which allows to write
25 short data objects with a reader to a tag and to read short data objects with a reader from a tag. The distance between the reader and the tag has typically to be a few centimeters. A device can be provided with both, a reader and a tag. The tag can be passive and the tag content can
30 have for instance a size of about 200 bytes.

For realizing the invention, the content of an RFID tag can be made use of in various ways.

In one alternative, the RFID tag is used in a conventional manner. That is, one device comprises an RFID tag storing a data packet, and an RFID reader in another device emits radio signals for causing an establishment of a connection. The RFID tag in the first device responds automatically with a stored data packet when both devices come close enough to each other.

In another alternative, a device may read the content of its own RFID tag and broadcast this content to its neighborhood. The broadcast may use, for example, Bluetooth™, WLAN, Ethernet or Infrared Data Association (IrDA) or a combination of thereof. Another device is then responsible of recognizing that it is being contacted and of measuring how close the device transmitting the content of its RFID tag is.

In both alternatives, the provided tag content could contain the final handle which is required for setting up a connection.

Usually, however, the content of an RFID tag by itself cannot provide sufficient data for creating a valid handle. First, the contents of the RFID tag have to reveal that it identifies an electronic device as opposed to, for example, a building or a room. Standardizing a specific RFID tag format for identifying devices according to the invention and for presenting their handles could permit this requirement to be met, but the resulting unit price for RFID tags might be prohibitive. Second, the address information required for the handle may change many times during the lifespan of an RFID tag. Updating the contents of the RFID tag would present another set of economic and technical challenges.

With some additional steps, however, RFID tags can be used in an easy way for detecting a hugging state and for allowing a handle to be obtained. The goal of those steps
5 is to map the content of the tag, for example an ID, into a usable address such as an IP-address.

The provided tag content may contain, for example, at least enough information so that the other device can
10 successfully respond, possibly with a broadcast of its own, thus opening a longer dialog for obtaining the handle.

In another embodiment, a received content of an RFID tag
15 may cause a device to query a local database for known tag contents and their known mapping to usable addresses, for example IP-addresses. Instead of a local database, also a centralized database can be used. Such a centralized database has the advantage that it can serve
20 a large number of devices and that it avoids the requirement that the devices have prior knowledge of each other.

As indicated further above, the handle may comprise in
25 addition to an address any other information that can be used to establish a communication channel and, once it has been established, to use it. The handle can include for example a port number, security tokens, shared secret keys or public keys, information on which coding is to be
30 used and information on when the established communication channel may be used. The handle may even include information originating from a third party, such as the price of using the communication channel. For example, for obtaining the handle, the connectivity

provider could be queried for the price, once the involved electronic devices have agreed or tentatively agreed upon using a specific connectivity technology or a specific connection provider for the communication
5 channel which is to be established.

A logic can be used for obtaining the necessary handle.

The communication channel, which is set up according to
10 the invention, may be based on any available communication technology and protocol, including for example Bluetooth™, WLAN, General Packet Radio Service (GPRS) and Universal Mobile Telecommunications Service (UMTS).

15 The selection of a specific communication channel among various available communication channels may be based on predetermined user preferences, in order to guarantee the best user experience. In some cases, it may also be
20 advisable, though, to base the selection on a user input.

In one embodiment of the invention, care is taken that an established link is sustained under changing conditions. The link may be may be switched for example from IP-over-
25 Bluetooth™ to GPRS, when two devices between which a Bluetooth™ connection had been established are no longer within the Bluetooth™ range.

Unless special care is taken, two devices in a hugging
30 state may each create a link between each other. Typically, such a double linking is undesirable. In one embodiment of the invention, therefore a resolution mechanism is provided which determines which one of the devices is to create the communication channel. The

resolution may, for instance, be carried out already when the handle is obtained. The result of the resolution may then be incorporated into the handle as information for a link creation portion of an electronic device.

5 Alternatively, certain electronic devices might not be able to create the communication channel at all. Further alternatively, both electronic devices may create a communication channel and one of them is then dropped again. Further alternatively, some computational method
10 is used for determining which one of the electronic devices shall create the communication channel. For example, the devices may compare their IP-addresses, and only the one with a "lower" or "higher" IP-address is responsible for creating the communication channel.

15 The created communication channel should be accessible to at least one application, should this at least one application desire to use it. The word application is to be understood in the widest possible sense including, for
20 example, operating systems, utility software, end-user applications and dedicated hardware. The application could even be a piece of functionality offered by the operating system or some other application.

25 In some cases, it may be obvious, which application or applications are to be allowed to use an established communication channel, for example because there is only a single application on the device. Otherwise, an application selection logic may be employed for selecting
30 which application or applications are to use an established communication channel.

In one embodiment of the invention, the respective application is selected which is currently receiving the

user input. Most known operating system support this approach. They identify an application currently receiving the user input under different names, like "foreground application", "active application",
5 "application with focus", etc.

Another way of selecting an application may be based on determining what kind of applications or data are supported by the respective other device.

10

The applications may be required for instance to register to some functional block of the device in order to utilize an established communication channel. All applications in the device may then register themselves
15 along with information about what kind of services or data they can produce, consume or otherwise share. Based on this information, an application can then be selected to be allowed to use an established communication channel. For instance, during a hugging state, the
20 selection logic in two devices between which a communication channel is established may determine which registered application has a counterpart application in the respective other device that is capable of sharing the indicated type of information.

25

In one embodiment of the invention, an electronic device could also launch, that is, invoke an application or some function of an already-running application, which is allowed to make use of a communication channel. For
30 example, an application or a certain function of an application may be triggered based on the contextuality of the currently selected user menu. That is, an application can be started automatically based on the

context of the current menu item, once a communication channel has been established.

When invoking an application or some function, additional
5 data may be provided which is to be used by the invoked application or function, for instance information on whether the antenna of the electronic device is pointing upwards or downwards.

10 In the proposed framework, a logic forming part of the additional control portion could control and execute the invoked application or function of at least one desired application or function. A very simple logic could be used for simply launching a selected application, while a
15 slightly more complex logic could first check whether the selected application is already running and launch it only in case it is not running. An even more complex logic could be involved in passing context-specific parameters to the application after it has been made sure
20 that it is already running.

Alternatively, a special invoking application similar to Corba could be employed for taking care that a selected application or function is invoked when necessary. The
25 invoking application may then receive some context-specific data and identify based on at least part of this data other applications or functions which are allowed to use an established communication channel. The invoking application then invokes the identified applications or
30 functions if necessary and passes the rest of the context-specific data, if any, to them. A logic would then only be required for selecting the applications and functions and for providing the context-specific data to the invoking application. Such a logic could also form

part of the additional control portion of the proposed framework.

5 An application which is allowed to use an established communication channel has to become aware when the communication channel is available for use or when it is requested by an application in another device to share data. This awareness can be achieved by a polling by the application, by notifications to the application, by
10 callbacks to the application, by broadcast to the application, etc.

If the application itself does not poll for an established communication channel and/or for a request to
15 share data, for example a link creation portion of a device may be responsible for informing the application about a new communication channel and about possible changes in the status of the communication channel. Alternatively, an application selection logic may be
20 responsible for informing a selected application about an established communication channel and/or a request to share information.

In one embodiment of the invention, an application is
25 notified about an established communication channel after a communication channel has been established. In a more complex embodiment, an application is first notified that a communication channel is to be established, and the actual creation of the communication channel is postponed
30 until a notified application indicates that it is ready to use the communication channel.

Once a communication channel has been established between at least two devices and applications in these at least

two devices are aware of the established communication channel, these applications may communicate and interact in an application specific way across the communication channel.

5

Pieces of functionality offered by the operating system or some other application which may be considered as an application are for example the well known cut-and-paste, drag-and-drop and copy-paste mechanisms, etc.

10

Existing operating systems and applications implement cut-and-paste, drag-and-drop mechanisms and the like in different ways. In one embodiment of the invention, the implementation is adapted to support a use of these

15

mechanisms as an application which may use a communication channel established in accordance with the invention. If a user starts a cut-and-paste, copy-paste or drag-and-drop operation on one device by using a user interface of one of these mechanisms, the user indicates thereby in such an adapted implementation that the mechanism is the application which is to be selected. If the user then hugs the device with another, or vice versa, the user may complete the operation on the other device, once the communication channel has been

20

25

established.

In one embodiment of the invention, also the applications may influence the content of the handle, for instance by interacting with the portion of the device detecting a hugging state. If this kind of implementation is used, the handle may also contain information which is only relevant to the involved applications in both devices. This part of the handle is also referred to as secondary handle. The handle may then comprise for instance an IP-

30

address enabling the creation of a communication channel and in addition a secondary handle relating to an Moving Picture Experts Group (MPEG) 4 stream and intended for an application supporting MPEG-4 streams.

5

In another embodiment of the invention, a secondary handle is exchanged between devices via the established communication channel, and thus separately from the original handle containing the address information.

10

The electronic devices according to the invention can make use of sensors not only for the actual detection of a hugging state, but also in various ways for influencing the employment of the established communication channel.

15

In one embodiment of the invention, for example, sensors are provided which detect whether the antenna of a mobile phone constituting one of the electronic devices points upwards or downwards. Such a sensor and an associated logic allows the user of the mobile phone to indicate the direction of a desired data transfer via a communication channel by tilting the antenna of a mobile phone upwards or downwards. Antenna up could mean that data is to be uploaded to the mobile phone and antenna down could mean that data is to be downloaded from the mobile phone, or vice versa.

20

25

30

Instead of tilting, obviously any other physical manipulation of an electronic device could be detected by appropriate sensors, such as squeezing, shaking or rotating the electronic device, establishing an absolute rotational position of the electronic device or a rotational position relative to another device, moving the electronic device with a certain absolute or relative

speed, moving the electronic device with a certain acceleration, etc. Any of these movements can then be evaluated by a logic in order to determine for instance a desired direction of a data transfer or the behavior of the involved applications etc.

If some information is passed to an application, like information on the direction in which the antenna of the device is pointing, this information may thus form as well the basis for a context dependent interaction or, at least, enable the application to behave in context specific way.

In an advantageous embodiment of a device according to the invention, the device comprises an expandable framework. The framework comprises the basic features of the device, including a touch detection portion and a link creation portion. In addition, various functional blocks can be added to the framework. Each functional block provides the logic for an additional service to the applications in the device, to applications in other devices or to the portions of other devices realizing the detection of a hugging state, the obtaining of a handle and/or the creation of a communication channel.

One possible additional functional block may provide a logic for realizing the above mentioned application selection. Another possible additional functional block may provide a logic for determining the direction of a data exchange in cases where the roles of the applications in the two devices has to be determined. Yet another possible additional functional block may provide a logic for determining the most suitable data format when sharing data via an established communication

channel. Yet another possible additional functional block may provide a logic for an authentication, an authorization and/or an audit/accounting functionality, or other security services.

5

The possible context specificity of the invention might also focus on the interface between applications of an electronic device and components of this electronic device realizing the invention, for example components of the proposed framework. If the data passing through this interface, for instance information on the direction in which the antenna of the device is pointing, or data on the behavior of the interface, for instance information about which application gets selected, varies depending on a state information or on an available input, the interaction is, or has the capability of being, context dependent.

A communication channel established in accordance with the invention can be released again in various ways.

In one embodiment of the invention, an application is able to allow or to force the communication channel to be closed.

25

Alternatively or in addition, the component of the device which is responsible for creating the communication channel may also be responsible for terminating the communication channel again based on some suitable logic. A communication channel could be terminated for example after a predetermined period of non-use of the established communication channel.

Alternatively or in addition, an established communication channel may be terminated when a hugging state is detected for a second time after a communication channel has been established. The second hugging between devices is detected in the same way as the first one, but triggers the termination of the communication channel. In the simplest implementation of this embodiment, the existence of a link between two devices determines whether a detected hugging state results in the establishment of a communication channel or in the termination of an existing communication channel.

Alternatively or in addition, the detection of a second hugging can also be combined advantageously with the above described embodiment for pieces of functionality like cut-and-paste. The detection of a second hugging allows the necessity for a repeated entry of the hugging state to be avoided when a series of copy or move operations is to be carried out. Instead, a first hugging is achieved as a part of the first operation, and all subsequent operations are based on the communication channel and the parameters of that hugging. During or after the last operation, a second hugging terminates the sequence and, if desired, the communication channel.

The use of a second hugging for terminating a communication channel, however, is limited to cases where the user remains near the other device for the duration of the connection or, at least, returns to the other device when it is time to terminate the connection.

The invention can also be employed for linking up several devices, for example in a row in some kind of a temporal daisy-chain.

In one embodiment of the invention more than two devices may even be allowed to enter a hugging state with a certain device at the same time. One device may for
5 example multicast or broadcast its desire to enter a hugging state to a number of devices, for instance via IrDA or Bluetooth™.

The possibility of linking of several devices could also
10 be implemented using application specific functional blocks. But since such a linking may be useful for various applications, it is well suited as a functional block of the above mentioned framework.

15 In a further embodiment of the invention involving several devices, one mobile device may be used for causing the establishment of a communication channel between two other devices, in particular two non-mobile electronic devices, by hugging both one after the other.

20 A user interface may be provided which enables a user to influence all or selected ones of the described functions.

25 Some selected embodiments of the invention are summarized in the following.

In a "Basic Touch-and-Share" embodiment, the user of a mobile device touches some other electronic device with
30 the mobile device. The user finds that one or more applications start to interact in an application specific way.

In a "Cut-Touch-Paste" embodiment, the user starts a cut-and-paste, copy-paste or drag-and-drop operation on one electronic device, touches one device with the other, and completes the operation on the other device.

5

In a "Touch only" embodiment, the user of a mobile device touches some other device with the mobile device. The user finds that the two devices are now connected, for instance that they have an IP-connectivity.

10

In a "Touch and toggle" embodiment, the "Touch only" embodiment is supplemented in that the established connection is disrupted when the involved electronic devices touch for a second time.

15

In "Variations of Touch" embodiments, a mobile device is used for pointing at another device or other devices instead of touching them. Alternatively, the mobile device is taken in close proximity of the other device or devices.

20

An important part of the Touch-and-Share concept is that while the Touch part is momentary, the Share part may continue for a long time. In the mentioned "Basic Touch-and-Share" embodiment, for example, touching a desktop computer with a media phone may result in dozens of megabytes of a picture file being uploaded from the mobile phone to the computer over a relatively slow link, like GPRS.

25

30

It is understood that any of the described embodiments of the invention can be combined and varied in many ways.

Further, any employed logic can be realized either in hardware or in software.

Other objects and features of the present invention will
5 become apparent from the following detailed description
considered in conjunction with the accompanying drawings.
It is to be understood, however, that the drawings are
designed solely for purposes of illustration and not as a
definition of the limits of the invention, for which
10 reference should be made to the appended claims. It
should be further understood that the drawings are not
drawn to scale and that they are merely intended to
conceptually illustrate the structures and procedures
described herein.

15

BRIEF DESCRIPTION OF THE FIGURES

- Fig. 1 schematically shows a block diagram of a minimal
implementation of the invention;
- 20 Fig. 2 is a flow chart illustrating an operation in the
embodiment of Figure 1;
- Fig. 3 schematically shows a block diagram of an
extended implementation of the invention;
- Fig. 4 is a flow chart illustrating an operation in the
25 embodiment of Figure 3;
- Fig. 5 schematically shows a block diagram of an
expandable implementation of the invention;
- Fig. 6 is a flow chart illustrating an operation in the
embodiment of Figure 5;
- 30 Fig. 7 is a flow chart illustrating an operation
involving three devices in the embodiment of
Figure 5; and
- Fig. 8 is a flow chart illustrating a context based
operation.

DETAILED DESCRIPTION OF THE INVENTION

Figure 1 schematically presents a block diagram with two
5 electronic devices 10, 20, which are enabled to create a
hugging-based ad-hoc connection between each other in
accordance with a first embodiment of the invention. At
least one of the electronic devices is a mobile device.

10 The first electronic device 10 comprises a touch
detection portion 11, a link creation portion 12 and at
least one application 13. The touch detection portion 11
further comprises physical means 14 for realizing the
hugging and a logic 15. The touch detection portion 11
15 may further have access to a local database 16, as
indicated in figure 1 by dotted lines. The database 16
maps known RFIDs to usable IP addresses. Moreover, a user
interface 17 may be connected to the link creation
portion 12, which is equally indicted by dotted lines. In
20 the current embodiment, the physical means 14 for hugging
include by way of example by an RFID chip, which is
integrated into the electronic device 10. The link
creation portion 12 has access to several link bearers
18.

25 For the second electronic device 20, no details are
shown. It may comprise the same components as the first
electronic device 10, but some functional components or
parts thereof may also be missing. It may have, for
30 example, no link creation portion, as long as it is able
to use a link created by the link creation portion 12 of
the first device 10. If IP addresses are used for
creating the ad-hoc connection, for instance, the second
device 20 could have only the usual IP stack without any

additional functionality besides a touch detection portion.

5 The creation of an ad-hoc connection between the first electronic device 10 and the second electronic device 20 of Figure 1 will now be described with reference to the flow chart of Figure 2.

10 In a first step, the touch detection portion 11 detects that it hugs another device 20 or that it is being hugged by another device 20. That is, the physical means 14 for hugging forward or forwards measurement results and/or received data to the logic 15 of the touch detection portion 11. The logic 15 then determines based on the
15 received information whether a hug is occurring.

If the electronic devices 10, 20 comprise respective RFID chips 14, the hugging detection may include detecting at one device a transmitted content of an RFID tag,
20 measuring how close the device transmitting the tag content is, and determining based on this information whether a hugging is taking place. For example, when the second device 20 broadcasts the content of its RFID tag to its neighborhood over Bluetooth™, WLAN, Ethernet or
25 IrDA, etc., or over a combination thereof, the RFID chip 14 of the first device 10 may detect this content. The logic 15 of the first device 10 determines based on the signal strength of the received tag content whether the transmitter of the tag content can be assumed to be close
30 and thus to be hugging the first electronic device 10.

In a further step, the logic 15 of the touch detection portion 11 obtains a handle comprising address information which can be used to address the second

electronic device 20. The address information is assumed by way of example to be an IP-address.

If a hugging is determined by way of an RFID tag, the logic 15 of the touch detection portion 11 may be caused to query the local database 16 for known tag contents and their mapping to usable IP addresses. An IP address associated in the database 16 to the received tag content is then used as a handle.

10

The touch detection portion 11 of the first electronic device 10 will typically not require a user input, except possibly for the actual hugging by putting the first electronic device 10 into a relation to the second electronic device 20 which is predetermined for a hugging.

15

The hugging state has only to be maintained until the required handle information, in the present case the RFID tag content, has been transmitted by the second electronic device 20 to the first electronic device 10.

20

Instead of an RFID chip, the physical means of both electronic devices 10, 20 could comprise be for example a material on the surface on both electronic devices enabling a galvanic contact. If both devices touch physically, the galvanic connection is detected and an IP-address of the second electronic device 20 can be transmitted via this galvanic connection to the first electronic device for use as a handle.

25

30

In a subsequent step, the obtained handle is forwarded by the touch detection portion 11 to the link creation portion 12, and the link creation portion 12 creates a

link between the first electronic device 10 and the second electronic device 20.

If the handle is or comprises an IP address, as in the
5 current example, the link creation portion 12 can use any available link bearer 18, that is, any available communication channel which ensures that the indicated IP address can be reached. The available link bearers 18 may
10 comprise for instance GPRS, dial-up modem, data cable connected to a desktop computer with Ethernet card, etc.

Typically, the link creation portion 12 does not require any input of the user either. In some cases, it may be advisable to allow an access by a user via a user
15 interface 17, for example for determining which one of the available link bearers 18 should be used. For the best user experience, though, the link bearer 18 should be selected based on predetermined user preferences.

20 If the second electronic device 20 comprises as well a link creation portion, it is advantageously avoided that the link creation portions of both devices 10, 20 create a communication channel between the two devices 10, 20. By way of example, each electronic device obtaining a
25 handle compares therefore for example an included IP-address with its own IP-address, and only if the included IP-address is lower than its own IP-address, the respective device is responsible for creating the link. This step is indicated by a decision step in Figure 2.

30

To be useful, the communication channel created by the link creation portion 12 must be accessible in some way to the at least one application 13, should this application desire to use the communication channel.

The link creation portion 12 may or may not be aware which applications 13 exist or are running, and it may or may not be responsible for informing the applications 13 about a new link and about possible changes in the status of the link. In Figure 2, a further step, in which the link creation portion 12 notifies an application 13 of the first electronic device 10 that a communication channel has been established, is therefore indicated by dotted lines. Alternatively, the at least one application 13 could poll, for example, itself for an established communication channel.

Then, the application or applications of the electronic devices 10, 20 may use the communication channel whenever needed. One application 13 may be for example a piece of functionality offering Cut-and-Paste or Drag-and-Drop operations. Such an application may be part of a more extensive application, in particular of an operating system. The implementation of this piece of functionality may be based on known implementations which are adapted to the invention. A user may select for instance an item for a Cut-and-Paste or Drag-and-Drop operation. As soon as the piece of functionality 13 implementing the Cut-and-Paste or Drag-and-Drop function is notified that a communication channel has been established, the piece of functionality 13 will transmit the selected item via the communication channel to the second electronic device 20.

The link creation portion 12 may monitor as well, whether the established communication channel should be terminated. In case of a timeout indicating that the communication channel has not been used for a

predetermined period of time, the communication channel is disconnected.

5 In a "Touch and Toggle" implementation, the link creation portion 12 may monitor in addition whether the detection of a second hugging is reported by the touch detection portion 11 while a communication channel exists. If such a second hugging is reported, the communication channel is equally disconnected.

10

The link creation portion 12 further monitors whether the conditions on the established communication channel deteriorate. In case the conditions become unacceptable, the link creation portion 12 switches the link to another
15 communication channel, if possible. The link creation portion 12 may switch for example from an IP-over-Bluetooth™ connection to a GPRS connection, when the two electronic devices 10, 20 are no longer within the Bluetooth™ range to each other.

20

The embodiment of the invention described with reference to Figures 1 and 2 may be employed in various situations, a few of which will be presented in the following.

25 In one possible situation, the first electronic device 10 could be for example a TV-set and the second electronic device 20 a mobile phone. A user may be watching a TV program on the TV-set, but has to leave home before it is finished. Before leaving, the user simply hugs the TV-set
30 with a mobile phone he will carry along. The TV-set detects the hugging, obtains a handle including the IP-address of the mobile phone, establishes a communication channel to the mobile phone, goes to stand-by and transmits the selected TV program via the established

communication channel to the mobile phone. The user may then continue watching the same TV program on the display of the mobile phone.

5 In another possible situation, the first electronic device 10 is a desktop computer and the second electronic device 20 is a laptop. An office worker has opened the disk management application of her desktop computer and selected a disk to share. Then, she causes a hugging
10 state between the computer and the laptop. The computer detects the hugging state, obtains a handle including the IP-address of the laptop and establishes a communication channel to the laptop. The laptop may then mount the disk via the established communication channel.

15 In another possible situation, the first electronic device 10 is a desktop computer and the second electronic device 20 is a mobile phone. A businessman may be in a rush to go to an airport and would like to download some
20 large files from his desktop computer to his mobile phone, which has a very slow connection. He opens a file management application on the computer, selects the desired files and clicks on an option which may be named "Send to Touch-and-Share". He then hugs the computer with
25 his mobile phone and rushes to his car. During the short hugging, the computer received from the mobile phone information for obtaining the IP-address of the mobile phone. Thereupon, the computer establishes a GPRS connection to the mobile phone, and an application starts
30 to download the selected files to the mobile phone via the established connection. By the time the businessman reaches the airport, the files have been downloaded to the mobile phone.

The distinction between the touch detection portion and the link creation portion is that the touch detection portion can rely on having a communications channel open between the two devices for the duration of creating the handle, while the link creation portion may not have such a channel available until the desired communication channel itself is created. This distinction is, however, not always completely obvious. For example, the physical communications channel used during a hugging may remain available even after the hugging state has been terminated. A hugging of two devices can be given if two devices are very close to each other, which can be detected for instance based on the timing or on the strength of radio signals received from the respective other device via a radio interface, but the devices may also be capable of communicating at a greater distance using the same radio interface. Also when RFID tags are used for detecting a hugging state, the distinction may not be obvious.

Figure 3 schematically presents a block diagram with two electronic devices 30, 40, which are enabled to create a hugging-based ad-hoc connection between each other in accordance with a second embodiment of the invention. At least one of the electronic devices is a mobile device.

The first electronic device 30 comprises components 31 to 38 which correspond to the components 11 to 18 of the first electronic device 10 of figure 1. In addition, however, it comprises an application selector 39 arranged between the link creation portion 32 and a plurality of applications 33.

For the second electronic device 40, no details are shown. It is assumed to comprises the same components as the first electronic device 30, even though some components could be missing.

5

The creation of an ad-hoc connection between the first electronic device 30 and the second electronic device 40 of Figure 3 will now be described with reference to the flow chart of Figure 4.

10

The creation of the ad-hoc connection is basically the same as described with reference to Figure 2. Since the application 33 which is allowed to use the created communication channel may not be obvious, however, the application selector 39 selects one or more applications 33 which are allowed to use an established communication channel. The application selector 39 includes to this end a selection logic.

15

20

By way of example, it is assumed that any application 33 has to register itself with the application selector portion 39 or some other component in order to utilize the "Touch-and-Share" functionality. An application 33 registers itself along with information about what kind of services or data it can produce, consume or otherwise share. For example, one application may be able to receive an MPEG-4 stream and another application may support a protocol interface recognizable by its Web Services Description Language (WSDL) URL.

25

30

Next, a hugging is detected and a handle obtained by the touch detection component 31 of the first electronic device 30 as described with reference to Figures 1 and 2.

In addition, the application selector 39 in both devices 30, 40 evaluate during the hugging state whether the devices 30, 40 have counterpart applications capable of producing and willing to share data with an application
5 in the respective other device. For instance, the application selector portion 39 in both devices 30, 40 may decide that an application supporting MPEG-4 in one device 30 has a counterpart application in the other device 40 which is able and willing to share an MPEG-4
10 stream. Thus, these applications are selected by the application selector portion 39 in both devices 30, 40.

Further, the application selector 39 in the respective device 30, 40 informs the selected applications 33 that a
15 communication channel will be created. The handle obtained by the touch detection portion 31 of the first electronic device 30 may comprise in addition to the address information required for a later link creation as well a secondary handle for the selected application, for
20 instance for the MPEG-4 stream, which may be used exclusively by the selected application. In this case, the application selector 39 forwards the secondary handle to the selected applications 33 when informing these applications 33 that a communication channel will be
25 created.

Then, the application selector 39 in the first electronic device 30 monitors whether it receives an indication by the selected applications 33 of the first electronic
30 device 30 that they are ready to use the offered communication channel. Upon such an indication, the application selector 39 causes the link creation portion 32 to create a communication channel to the second

electronic device 40 based on the address in the obtained handle.

5 The further operation may be similar as the operation in the first embodiment described with reference to Figure 2.

Alternatively or in addition, the application selector 39 could select the application 33 which is currently
10 receiving a user input, if the operating system of the electronic device 30 supports this approach by registering this application as "foreground application", "active application", "application with focus", or the like.

15 The actual interaction on an established communication channel is context specific. For example, a user of a first mobile phone may want to share ten large files with the user of a second mobile phone. The user of the first
20 mobile phone marks the files on her mobile phone for copy-and-paste and defines thereby a context. The user of the first mobile phone then touches the second mobile phone with her mobile phone. The touch should require less than one second. By the touch, a context specific
25 share is triggered. The share may happen independently of location, time limitations and user input based on user preferences. The user of the second mobile phone rushes to the airport, while the files are downloaded to his mobile phone.

30 The embodiment of the invention described with reference to Figure 3 may also be employed in scenarios involving multiple devices.

In one exemplary scenario, the electronic devices are gaming devices which are employed for a mobile multiplayer game exhibiting a linking of multiple gaming devices. In a certain situation, a group of persons is
5 playing the mobile game over Bluetooth™. A further person joins the group and hugs the gaming device of one of the players with his own gaming device. In the gaming device of the player, the touch detection portion 31 detects a hugging state and obtains a handle, the link creation
10 portion creates a communication channel, and the application selector 39 notifies the active application 33. Using the created communication channel, the same game is invoked thereupon by the notified application in the device of the further person via the established
15 communication channel. The game may even be downloaded to his device, if necessary.

Figure 5 schematically presents an electronic device, which is enabled to create a hugging-based ad-hoc
20 connection with another electronic device in accordance with a third embodiment of the invention.

The electronic device 50 comprises in contrast to the embodiments of figures 1 and 3 an extendable framework
25 with partly variable functional blocks.

The framework comprises like the electronic devices of figures 1 and 3 a touch detection portion 51, a link creation portion 52 with access to link bearers 58 and
30 applications 53. In addition, however, it comprises an additional control logic portion 60 which is responsible for enforcing the logic needed to provide additional services which a particular implementation of the electronic device 50 may provide to the applications 53

in the device 50 or in other devices, or to the implementation in general of other devices.

5 The touch detection portion 51, the link creation portion 52 and the applications 53 have access to the additional control logic portion 60. In addition, a user interface UI 66 and sensors 67 are connected to the additional control logic portion 60. Further components 68 may
10 60.

For providing the desired services, the additional control logic portion 60 itself may include various functional blocks. Several exemplary blocks are indicated
15 in figure 5.

The exemplary functional blocks include an application selector 61, which can have similar functions as the application selector 39 of the first electronic device 30
20 of figure 3. The application selector 61 might also be split further into two functional blocks. One block could then be responsible for selecting the application 53 that is allowed to use an established communication channel, while the other block could be responsible for producing
25 an application specific secondary handle. Such a split-up enables a better modularity and a better integration with a Drag-and-Drop functionality, a Copy-Paste functionality, etc.

30 The exemplary functional blocks of the additional control logic portion 60 further include an AAA block 62, which provides an authentication, authorization and audit/accounting functionality along with other security services that may be needed by in a "Touch-and-Share"

operation or by some of the applications 53, unless such a functionality is implemented in these applications themselves. If the electronic device 50 belongs to a service provider, for example, the AAA block 62 might
5 determine based on the IP address of a handle obtained during a hugging state with some other electronic device, whether this device is authorized to access a certain service and which charging rates are to be applied. For the authentication etc., also additional information
10 might be exchanged during the hugging state between the AAA block 62 and the other electronic device via the touch detection portion 51.

The exemplary functional blocks of the additional control
15 logic portion 60 further include a directional logic 63. This directional logic 63 provides a logic for determining the direction of share via the communication channel in those cases, in which the roles of involved applications in two devices has to be determined. For
20 example, if an FM-radio-equipped device touches an FM radio, it has to be determined which one gets tuned to the frequency of the other. The respective choice of a direction by the directional logic 63 could be based on user preferences, device preferences, randomness, a user
25 input via the user interface 66 or measurement data provided by the sensors 67, etc. In absence of a directional logic 63, a similar functionality may have to be implemented on an application basis.

30 The exemplary functional blocks of the additional control logic portion 60 further include a data format selector 64, which provides a logic which enables the applications 53 to find the most suitable data format when sharing data via an established communication channel. The

functionality of this block can be realized similarly as the "Paste Special..." functionality in some office applications.

- 5 Any other functional block 65 realizing a desired function can be integrated as well in the additional control logic portion 60.

The user interface 66 can be used by any of the
10 functional blocks 61 to 65 in the additional control logic portion 60, in order to involve the user in the logic or functioning of the respective block. The user interface 66 can equally be used by the Touch Detection portion 51 and/or the Link Creation portion 52 if
15 desired.

Moreover, sensors 67 may be used for supporting various functions.

- 20 One implementation of the electronic device 50 uses the sensors 67 in combination with the directional logic 63 in the electronic device 50 for influencing the sharing behavior, as illustrated in the flow chart of Figure 6. The embodiment is used for "pouring" data from one
25 electronic device to another.

One electronic device is assumed to be a mobile phone and the other one a computer. Both may be implemented as described with reference to Figure 5. The active
30 application in both devices presents a view of a file folder.

In a first step, a user selects via a user interface a number of files on one or on both devices. The selection can be performed for example by highlighting the files.

- 5 Then, at least the touch detection component 51 of the mobile phone detect a hugging with the computer, as described above.

During the hugging, the sensors 67 of the mobile phone
10 determine whether the antenna of the mobile phone is pointing upwards or downwards and forward this information to the directional logic 63 of the mobile phone.

- 15 The sensors 67 of the mobile phone determine in addition whether the mobile phone is shaken during the hugging and forward this information as well to the directional logic 63 of the mobile phone.

20 If it is detected that the antenna of the mobile phone is pointing upwards and that the mobile phone is not shaken during the touch, it is determined by the directional logic 63 of the mobile phone that the user desires to copy the selected files from the computer to the mobile
25 phone, if a copy-mode is active. If a move-mode is active, the directional logic 63 of the mobile phone determines that the user desires to move the selected files from the computer to the mobile phone.

30 If it is detected that the antenna of the mobile phone is pointing upwards and that the mobile phone is shaken during the touch, it is determined by the directional logic 63 of the mobile phone that the user desires to move the selected files from the computer to the mobile

phone, if a copy-mode is active. The directional logic 63 switches to a move-mode. If a move-mode is active, the directional logic 63 of the mobile phone determines that the user desires to copy the selected files from the computer to the mobile phone. The directional logic 63 switches to a copy-mode.

If it is detected that the antenna of the mobile phone is pointing downwards and that the mobile phone is not shaken during the touch, it is determined by the directional logic 63 of the mobile phone that the user desires to copy the selected files from the mobile phone to the computer, if a copy-mode is active. If a move-mode is active, the directional logic 63 of the mobile phone determines that the user desires to move the selected files from the mobile phone to the computer.

If it is detected that the antenna of the mobile phone is pointing downwards and that the mobile phone is shaken during the touch, it is determined by the directional logic 63 of the mobile phone that the user desires to move the selected files from the mobile phone to the computer, if a copy-mode is active, thereby entering a move-mode. The directional logic 63 switches to a move-mode. If a move-mode is active, the directional logic 63 of the mobile phone determines that the user desires to copy the selected files from the mobile phone to the computer. The directional logic switches to a copy-mode.

Then, the link creation portion 52 of one of the devices creates a communication channel as described above. Further, the application selectors 61 of both devices notify the file management system within the operating system of each device as relevant applications that a

link has been created and about the desired kind of data exchange.

5 The file management systems exchange thereupon data via the respective application selector 61, the respective link creation portion 52 and the link bearer 58 used for the created communication channel as requested.

10 If a further hugging is performed, the copy-mode can be transformed into a move-mode and vice versa by shaking the mobile phone during the hugging.

15 A scenario involving multiple devices for realizing a temporal, and possibly spatial, piggyback is illustrated in the flow chart of Figure 7.

A first device A contains some files.

20 A second device B is used to hug device A, or vice versa, recognizes that device A is willing to share those files, and obtains handle information. The handle information include information on an address, for instance an IP address, of device A and some pointers to the actual files, for instance URLs.

25 Device B is then used at some later time to touch a third device C. During the touch, the handle information is forwarded by device B to device C. A functional block in an additional control logic portion in device B is
30 responsible for obtaining the handle information from device A and for forwarding it to device C.

Device C now sets up a communication channel to device A making use of the obtained handle.

Finally, device C obtains a copy of the files identified by the pointers via the established communication channel from device A.

5

In another embodiment of the invention, the current menu item is evaluated for triggering an application, as illustrated in the flow chart of Figure 8.

- 10 In this embodiment, the user of an electronic device selects another electronic device by simple pointing to the other device and therefore getting very small distance between the two devices. This resolves the device selection and addressing problem. Further on, an
15 application is started automatically based on the context of the current menu item.

The device comprises a close proximity indicator which determines a close proximity to another device.

- 20 Currently, there are mainly two alternatives which would suit the requirements of small devices, namely RFID and Bluetooth™. Most RFID technologies work only over the distance of a few centimeters and would thus be suited for determining a proximity between two devices. But also
25 Bluetooth™ could be used for determining a proximity by analyzing the RSSI measurements which chipsets compliant to the Bluetooth 1.2 specifications are providing. The close proximity indicator could also be realized like the touch detection portion in the preceding embodiments.
30 Moreover, a communication channel to another device may be created based on a handle as described for the preceding embodiments.

The device further comprises a component for triggering a desired function based on a trigger from the close proximity indicator and the current menu item. If a trigger from the close proximity indicator comes, this component evaluates the current menu item and determines the intended end user action. Such a component could also be a functional block in the additional control logic portion of the device of Figure 5.

10 The function related to the intended end user action is then performed.

A potential use case is that a person takes a picture and wants to share it with another person close by. The picture is on the menu screen and a single menu item puts the device into a sharing mode. If the device now comes close enough to a second device, "sharing the picture" is recognized as desired action. The picture is then transferred automatically to the other device, as the intention to share the item with the other device is already expressed by pointing to the other device. Even the single key press to put the device into the sharing mode is not always needed, as the unintentional pointing to another device is not typical, and therefore the sharing could be triggered also without any further user interaction.

While there have been shown and described and pointed out fundamental novel features of the invention as applied to a preferred embodiment thereof, it will be understood that various omissions and substitutions and changes in the form and details of the devices and methods described may be made by those skilled in the art without departing from the spirit of the invention. For example, it is

expressly intended that all combinations of those elements and/or method steps which perform substantially the same function in substantially the same way to achieve the same results are within the scope of the invention. Moreover, it should be recognized that structures and/or elements and/or method steps shown and/or described in connection with any disclosed form or embodiment of the invention may be incorporated in any other disclosed or described or suggested form or embodiment as a general matter of design choice. It is the intention, therefore, to be limited only as indicated by the scope of the claims appended hereto.